

Premier

	Premier 170	Premier 350	Premier 80
Heat Rating			
Intermediate Input/Output (Btu/h)	-	175,000	-
Max (Input/Output) (Btu/h)	170,000	350,000	80,000
Configurations Available			
Ignition Type	Direct Spark	Direct Spark	Direct Spark
Heated Air Output			
Heated Air Output (CFM)	1200	2400	450
Fuel Consumption (max)			
LPG (lbs./hr.)	7.9	16.2	3.7
NG (cu. ft./hr.)	170.0	350.0	80
Inlet Gas Pressure			
LPG min/max (W.C.)	11.0 / 13.5	11.0 / 13.5	11 / 13.5
NG min/max (W.C.)	7.0 / 13.5	7.0 / 13.5	7 / 13.5
Electrical Supply			
Amps (Starting/Cont. Oper.)	8 / 2.5	30.0 / 14.0	5 / 1.5
Electrical Requirements (Volts/Hz/Phase)	115 / 60 / 1	115 / 60 / 1	115 / 60 / 1
Dimensions			
Height (in.)	28.0	41.0	20.0
Length (in.)	31.0	48.0	29.5
Width (in.)	18.0	22.0	13.5
Weight			
Net Weight (lbs.)	126	295	67
Shipping Weight (lbs.)	134	320	74
Materials			
Case Material	Tri-Shield Steel	Tri-Shield Steel	Tri-Shield Steel
Add'l Features/Options			
Ducting	Opt.	Opt.	Opt.
End Diffuser	Opt.	Opt.	Opt.
Gas Hose (10ft U.S./15ft. Can)	Std.	N/A	Std.
Gas Hose (15ft U.S./15ft. Can)	N/A	Std.	N/A
Gas Pressure Regulator (with POL)	Std.	Std.	Std.
Thermostat (w/ 20 ft cord)	Std.	Std.	Std.
Unit Diffuser	Opt.	Opt.	Opt.
Certifications			
CSA-Canada	Yes	Yes	Yes
CSA-U.S.	Yes	Yes	Yes